



#### Notes:

1. \* Helvetica bold or equivalent.
2. \*\* Stop number (if ordered).
3. \*\*\* Company logo (if ordered).
4. Sign face to be double sided.
5. 2 holes to suit Type 1 sign bracket as per standard drawing No. 1295, ES126-1996.
6. Material: 1.2 mm thick aluminium or equivalent zincanneal or Simona PVC plastic 6mm thick.

#### Colour Legend

- Class 2 retroreflective blue (background)
- Class 2 retroreflective white (legend, symbol and border)



**Queensland Government**  
Department of **Main Roads**

## BUS STOP SIGN

Traffic & Road Use Management Division  
Traffic Engineering Section

ORIGINAL APPROVED AS OFFICIAL TRAFFIC SIGN

*[Signature]*  
PRINCIPAL ENGINEER  
(Traffic Engineering)

19/11/98  
Date

**TC1072**

Page 1 of 2

Designed  
RH 11/98

Checked  
JD 11/98

Scale  
Not to Scale

A ☐ ☐ ☐ ☐ ☐

Sign screen painted  
both sides

Galvanised cap  
inserted in top of the post

Type 1 sign bracket  
as per standard drawing  
No. 1295, ES126-1996



2000 clear

50 NB medium gauge  
galvanised pipe  
(overall length 2950)

Footpath

450  
min  
level

Kerb face  
(or road  
shoulder edge  
if no kerb)

450



**Queensland Government**  
Department of **Main Roads**

## BUS STOP SIGN

Traffic & Road Use Management Division  
Traffic Engineering Section

ORIGINAL APPROVED AS OFFICIAL TRAFFIC SIGN

*[Signature]*  
PRINCIPAL ENGINEER  
(Traffic Engineering)

19/11/98  
Date

**TC1072**

Page 2 of 2

Designed  
RH 11/98

Checked  
JD 11/98

Scale  
Not to Scale

A ☐ ☐ ☐ ☐ ☐