



Colour Legend

	Retroreflective white
	Retroreflective green
	Retroreflective yellow
	Black

	W5-47		TC1608		a	b	c	d	e	f	r ¹	r ²
A	600	600	600	400	1120	1440	48	24	95	105	120	100
B	750	750	750	500	1400	1800	64	32	120	130	200	100
C	900	900	900	600	1680	2160	80	40	145	155	225	100

Notes

1. This sign and flashing light panel may be used at locations where a higher impact wildlife warning device is warranted.
2. This assembly must be installed with a radar device capable of detecting vehicle speeds and triggering the flashing lights. The radar device must also have a time based functionality built in so that it will only trigger the flashing lights at prescribed times. Suggested hours of operation are 4pm - 8am but may vary.
3. The flashing lights shall operate alternately when activated by an approaching vehicle which is exceeding a nominated speed within the nominated prescribed times of operation. The flashing lights will continue to flash until the vehicle speed reduces to below the trigger speed or the vehicle continues past the sign.
4. The triggering speed is generally set as the 85th percentile speed or the actual speed limit plus 2 km/h whichever is the greater.
5. The radar system must be capable of recording data such as date, time and speed of all vehicles approaching at a set distance from the sign.
6. * Other wildlife warning signs may be used when appropriate.



**Queensland
Government**

WILDLIFE WARNING SIGN

"VEHICLE ACTIVATED FLASHING LIGHTS"

Department of Transport and Main Roads
Infrastructure Management & Delivery Division

APPROVED AS OFFICIAL TRAFFIC SIGN

TC1921

Designed
TV 11/11

Checked
DJ 03/20

Scale
Not to Scale

PRINCIPAL ENGINEER
(Traffic Engineering)

13/03/20
Date

A	B			
---	---	--	--	--