



Example

#### Colour Legend

	Retroreflective white
	Retroreflective blue
	Retroreflective yellow

	a	b	b <sub>max</sub>	c	d	e	f	g	h	k	m	n	o	p	q	r <sub>1</sub>	r <sub>2</sub>
TC1345_1A (Single lane roadway)	2400	1200	1800	400	20	16	250	140Em	40	72	50	110	55	90	90	200	50
TC1345_1B (Dual lane roadway)	3600	1800	2400	600	30	24	375	210Em	60	108	75	165	82	140	135	300	75
TC1345_1C (Motorway)	4800	2400	3000	800	40	32	500	280Em	80	144	100	220	110	190	180	400	100

#### Notes:

- This sign may be installed as an alternative to the MUTCD G6-1 Town Name sign. If an image is not required and the town is not a state strategic touring route, TC1692 may be used in lieu.
- \*1 - Insert appropriate town name. Text to be Helvetica Bold or equivalent. If the name is longer than the space allowed, email [TrafficEngineering.support@tmr.qld.gov.au](mailto:TrafficEngineering.support@tmr.qld.gov.au) for assistance.
- \*2 - Insert appropriate destination name of the next accredited Visitor Information Centre (VIC) which may be the same as the town name above. If it is longer than the space allowed, email [TrafficEngineering.support@tmr.qld.gov.au](mailto:TrafficEngineering.support@tmr.qld.gov.au) for assistance.
- \*3 - Insert appropriate distance to the VIC in kilometres.
- The visitor information centre panel must be installed with the welcome to town sign for towns which have an accredited VIC. It is optional for towns which do not have a VIC and if desired may be installed either with the welcome to town sign or as a stand-alone sign a short distance after the welcome sign.
- The white on blue roman "i" is not to be used as a substitute for the yellow italic "i".
- # - Text to be Helvetica Bold or equivalent.
- # - Dimension "k" for the image height may be increased if required to suit the approved image. In this case, dimension "b" will also be increased by the same amount. The increase of total height of the sign is not to exceed dimension b<sub>max</sub>.
- Image is to be a single high resolution image.
- The image must be approved and supported by both the relevant Regional Tourism Organisation (RTO) and local government.
- Image to be printed on a transparent overlay on a Class 1W retroreflective white background.
- Protective overlay film is recommended for this sign (excluding the VIC panel).
- Where single lane, dual lane and motorway signs are required, utilise TC1345\_1A, TC1345\_1B and TC1345\_1C signs respectively.
- Where signs with a tourist slogan may be required, refer to Page 2.



Example

#### Colour Legend

	Retroreflective white
	Retroreflective blue
	Retroreflective yellow

	a	b	b <sub>max</sub>	c	d	e	f	g	h	k	m	n	o	p	q	r <sub>1</sub>	r <sub>2</sub>
TC1345_2A (Single lane roadway)	2400	1400	2000	400	20	16	250	140Em	40	730	60	100	90	40	85	95	50
TC1345_2B (Dual lane roadway)	3600	2100	2700	600	30	24	375	210Em	60	1095	90	135	120	85	140	300	75
TC1345_2C (Motorway)	4800	2800	3400	800	40	32	500	280Em	80	1460	120	200	180	280	110	400	100

#### Notes:

- This sign may be installed as an alternative to the MUTCD G6-1 Town Name sign. An image is not required and the town is not a state strategic touring route, TC1692 may be used in lieu.
- \*1 - Insert appropriate town name. Text to be Helvetica Bold or equivalent. If the name is longer than the space allowed, email TrafficEngineering.support@tmr.qld.gov.au for assistance.
- \*2 - Insert appropriate tourist slogan. Text to be Helvetica or equivalent. The tourist slogan must be approved and supported by both the relevant Regional Tourism Organisation (RTO) and local government.
- \*3 - Insert appropriate destination name of the next accredited Visitor Information Centre (VIC) which may be the same as the town name above. If the name is longer than the space allowed, email TrafficEngineering.support@tmr.qld.gov.au for assistance.
- The visitor information centre panel must be installed with the welcome to town sign for towns which have an accredited VIC. It is optional for towns which do not have a VIC and if desired may be installed either with the welcome to town sign or as a stand-alone sign a short distance after the welcome sign.
- The white on blue roman "i" is not to be used as a substitute for the yellow italic "i".
- \*4 - Insert appropriate distance to the VIC in kilometres.
- \*5 - Text to be Helvetica Bold or equivalent.
- \*6 - Text to be Helvetica or equivalent.
- \*7 - Dimension "k" for the image height may be increased if required to suit the approved image. In this case, dimension "b" will also be increased by the same amount. The increase of total height of the sign is not to exceed dimension b<sub>max</sub>.
- Image is to be a single high resolution image.
- The image must be approved and supported by both the relevant Regional Tourism Organisation (RTO) and local government.
- Image to be printed on a transparent overlay on a Class 1W retroreflective white background.
- Protective overlay film is recommended for this sign (excluding the VIC panel).
- Where single lane, dual lane and motorway signs are required, utilise TC1345\_2A, TC1345\_2B and TC1345\_2C signs respectively.
- Where signs without a tourist slogan may be required, refer to Page 1.



Queensland  
Government

Department of Transport and Main Roads  
Infrastructure Management & Delivery Division

APPROVED AS OFFICIAL TRAFFIC SIGN

PRINCIPAL ENGINEER  
(Traffic Engineering)

18/12/20  
Date

TOWN WELCOME SIGN  
WITH IMAGE &  
TOURIST SLOGAN

TC1345\_2  
Page 2 of 2

Designed  
RH 12/01

Checked  
DJ 12/20

Scale  
Not to Scale

0 P