



Colour Legend

- Black (borders and top panel legend)
- Retroreflective white (bottom panel legend)
- Retroreflective red (bottom panel background)
- Retroreflective yellow (top panels background)

Notes:

1. External borders to be a folded metal frame as normally used in a temporary sign.
2. * Internal borders to be marked only.
3. Sign to be displayed on a temporary basis at approved (AWE) stock crossing locations.
4. Sign to be located on the road shoulder and on appropriate supports, approximately 2D from the stock crossing (where D= speed limit in km/h).
5. Sign to be displayed immediately prior to stock crossing the road and is to be removed immediately following the completion of stock crossing activities.
6. If the sign is to be used multiple times during the day it may be covered by approved methods when not in use.
7. Where stock crossing points are used more frequently, consider installing fixed hinged sign TC1690.
8. Refer TRUM technical note 1.19 for further information.



Queensland Government
Department of **Main Roads**

Planning, Design and Operations Division
Traffic Engineering Section

Designed
TV 01/08

Checked
DJ 01/08

Scale
Not to Scale

TEMPORARY WARNING SIGN "STOCK CROSSING AHEAD"

ORIGINAL APPROVED AS OFFICIAL TRAFFIC SIGN


PRINCIPAL ENGINEER
(Traffic Engineering)

30/01/08
Date

TC1691

A